(in accordance with Regulation (EU) 2015/830)

## Concrete Finish WT B

Date of compilation: 16/11/2016 Version 1

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 1 of 9

Print date: 23/04/2021

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Concrete Finish WT B Product Name:

## 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Hardener (component B) for two-component water based polyurethane sealer.

### Uses advised against:

Uses other than those recommended.

### 1.3 Details of the supplier of the safety data sheet.

**Luxury Concrete, SLU** Company:

Address: C/ Lepanto n 9, 3a 46008, Valencia City: Province: Valencia

Telephone: +34 910 028 940 E-mail: info@luxuryconcrete.eu Web: https://www.luxuryconcrete.eu/

1.4 Emergency telephone number: +34 630 352 217 (Available 24 hours)

### **SECTION 2: HAZARDS IDENTIFICATION.**

## 2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Resp. Sens. 1: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1: May cause an allergic skin reaction.

### 2.2 Label elements.

## Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



### Signal Word:

## **Danger**

H statements:

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

P statements:

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P284 [In case of inadequate ventilation] wear respiratory protection.

P501 Dispose of contents/container to ...

**EUH statements:** 

**EUH204** Contains isocyanates. May produce an allergic reaction.

(in accordance with Regulation (EU) 2015/830)

## **Concrete Finish WT B**

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 2 of 9 Print date: 23/04/2021

Contains:

hexamethylene-di-isocyanate

Hexamethylene diisocyanate, oligomers

#### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
CAS No: 28182-81-2 EC No: 500-060-2	Hexamethylene diisocyanate, oligomers	1 - 99.99 %	Skin Sens. 1, H317	-
Index No: 615-011- 00-1 CAS No: 822-06-0 EC No: 212-485-8 Registration No: 01- 2119457571-37-XXXX	[1] hexamethylene-di-isocyanate	0.5 - 9.99 %	Acute Tox. 3, H331 - Resp. Sens. 1, H334 - Skin Sens. 1, H317	Resp. Sens. 1, H334: C ≥ 0,5 % Skin Sens. 1, H317: C ≥ 0,5 %

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

## **SECTION 4: FIRST AID MEASURES.**

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

## Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

### Eve contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

It may cause an allergic reaction in the respiratory system. Chronic exposure can lead to asthma.

## 4.3 Indication of any immediate medical attention and special treatment needed.

<sup>[1]</sup> Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

## **Concrete Finish WT B**

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 3 of 9

Print date: 23/04/2021

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. If the person vomits, clear the respiratory tract. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

## 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

## 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## **SECTION 7: HANDLING AND STORAGE.**

### 7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

## 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from

(in accordance with Regulation (EU) 2015/830)

## **Concrete Finish WT B**

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 4 of 9

Print date: 23/04/2021

oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once

the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### 7.3 Specific end use(s).

For professional use.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
hexamethylene-di-isocyanate	822-06-0	Éire [1]	Eight hours	0,005	
nexametriylene-ur-isocyanate			Short term		

[1] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
hovamathylana di isasyanata	DNEL	Inhalation, Long-term, Local effects	0,035
hexamethylene-di-isocyanate	(Workers)		(mg/m³)
CAS No: 822-06-0 EC No: 212-485-8	DNEL	Inhalation, Long-term, Systemic effects	0,035
EC NO: 212-405-0	(Workers)		(mg/m³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

## 8.2 Exposure controls.

## Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Hardener (component B) for two-component water based polyurethane sealer.			
Breathing protection:				
PPE:	Filter mask for protection against gases and particles.			
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.			
CEN standards:	EN 136, EN 140, EN 405			
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach			
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.			
Filter Type needed	: A2			
Hand protection:				
PPE:	Protective gloves against chemicals.			
Characteristics:	«CE» marking, category III.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.			
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.			
	Always use with clean, dry hands.			
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35			
Eye protection:				

(in accordance with Regulation (EU) 2015/830)

## Concrete Finish WT B

Date of compilation: 16/11/2016 Version 1

Page 5 of 9 Version 3 (replaces version 2) Revision date: 31/03/2021 Print date: 23/04/2021

PPF: Protective goggles with built-in frame.

«CE» marking, category II. Eye protector with built-in frame for protection against Characteristics:

dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168

Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance:

be disinfected periodically following the manufacturer's instructions.

Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, Observations:

scraping etc.

Skin protection: PPE: Protective clothing.

«CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics:

order not to obstruct the user's movements.

CEN standards: EN 340

Observations:

In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance:

the manufacturer.

The protective clothing should offer a level of comfort in line with the level of protection provided in

terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level

of activity and the expected time of use.

PPF. Work footwear.

Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 CFN standards:

This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should Maintenance:

not be used by other people.

Work footwear for professional use includes protection elements aimed at protecting users against any Observations:

injury resulting from an accident

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

### 9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: amarillento Odour:casi inodoro Odour threshold: N.A./N.A. pH:N.A./N.A. Melting point: N.A./N.A.

Boiling Point: N.A./N.A. Flash point: 185 °C Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density: N.A./N.A. Relative density: 1.15 Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: inmiscible

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information. Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

## **SECTION 10: STABILITY AND REACTIVITY.**

-Continued on next page.-

(in accordance with Regulation (EU) 2015/830)

## Concrete Finish WT B

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 6 of 9 Print date: 23/04/2021

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

### 10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

#### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.

## **SECTION 11: TOXICOLOGICAL INFORMATION.**

### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Exposure to concentrations of solvent fumes above the work exposure limit can have negative effects (for example, irritation of the mucous membranes and respiratory system, adverse effects on the kidneys, liver, and the central nervous system). Among the symptoms are headaches, vertigo, fatigue, muscular weakness, drowsiness, and in extreme cases, unconsciousness.

Based on the properties of isocyanates and taking into account existing technical data on similar products, it appears that this product may cause irritation and / or acute awareness of the respiratory system, leading to an asthmatic condition, a wheezing and chest pressure. Therefore, sensitized individuals may show asthmatic symptoms when exposed to atmospheres containing concentrations below the level of exposure. Repeated exposure can lead to chronic respiratory diseases.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Product classified:

Respiratory sensitiser, Category 1: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

## **Concrete Finish WT B**

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 7 of 9 Print date: 23/04/2021

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

## **SECTION 12: ECOLOGICAL INFORMATION.**

### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

## 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## **SECTION 13: DISPOSAL CONSIDERATIONS.**

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

(in accordance with Regulation (EU) 2015/830)

## **Concrete Finish WT B**

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 8 of 9

Print date: 23/04/2021

#### 14.1 UN number.

Transportation is not dangerous.

### 14.2 UN proper shipping name.

Description:

ADR: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

### 14.3 Transport hazard class(es).

Transportation is not dangerous.

### 14.4 Packing group.

Transportation is not dangerous.

#### 14.5 Environmental hazards.

Transportation is not dangerous.

### 14.6 Special precautions for user.

Transportation is not dangerous.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

### **SECTION 15: REGULATORY INFORMATION.**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): j - Two-pack reactive performance coatings for specific end use such as floors, water-horne

Phase I\* (from 01/01/2007): 140 g/l Phase II\* (from 01/01/2010): 140 g/l

(\*) g/l ready to use

VOC content (p/p): 0 % VOC content: 0 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): nwg: Not dangerous to water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(in accordance with Regulation (EU) 2015/830)

## **Concrete Finish WT B**

Version 1 Date of compilation: 16/11/2016

Version 3 (replaces version 2) Revision date: 31/03/2021



Page 9 of 9

Print date: 23/04/2021

### Classification codes:

Acute Tox. 3: Acute toxicity (Inhalation), Category 3

Eye Irrit. 2: Eye irritation, Category 2

Resp. Sens. 1: Respiratory sensitiser, Category 1

Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Addition of abbreviations and acronyms (SECTION 16).

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

AwSV: Facility Regulations for handling substances that are hazardous for the water.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

PPE: Personal protection equipment.

WGK: Water hazard classes.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.