

Concrete Resin Pool.

Concrete Resin Pool is a water-based acrylic resin designed for Concrete Pool microcement swimming pools. Its function is to provide adhesion, hardness and flexibility to microcement coatings while maintaining their water vapour permeability and water repellency.



Properties

Liquid component for the mixing of the two-component swimming pool microcements Luxury®:

- Excellent substrate stabilisation.
- Water-based, non-flammable.
- The product is supplied ready for use.
- Increases mechanical resistance.
- Increases the impermeability of the mortar, being permeable to water vapour.
- Reduces the appearance of shrinkage cracks.
- Low water absorption.

Application

- Pour a little resin into a container, add the entire load of pigment corresponding to the amount of microcement to be worked with and mix until a homogeneous liquid colour is obtained.
- Pour the powdered swimming pool microcement gradually while mixing the product
- Mix for at least 4 minutes until a homogeneous, lump-free mixture is obtained.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.
In case of contact with skin wash with soap and water.

Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.
Keep out of reach of children.

The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with current legislation.

To prevent the product from drying out or thickening, close the lid after each use.

Application temperature between 10°C and 30°C.

This product is not toxic, dangerous or flammable, under normal handling conditions. This product does not contain any harmful substances that would require, under the current regulations, any additional labelling measures.

Mixing

Concrete Pool resin is mixed with Luxury® swimming pool microcements.

In order to guarantee the properties of the coating, it will be essential to respect the ratio between the microcement and the resin.

- 10 kg Concrete Pool Medium - 2,0 L Concrete Resin Pool
- 10 kg Concrete Pool GrandL - 1,8 L Concrete Resin Pool

Consumption

Consumption for Concrete Resin Pool:

- 0,10 L/m², varying according to the porosity of the substrate.

Storage conditions

It should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.

Packaging

It is packaged in 25 litre cans.

Cleaning of tools

Tools are washed with soap and water immediately after use.