(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Version 1 Date of compilation: 16/11/2016

Version 4 (replaces version 3) Revision date: 31/03/2021



Page 1 of 10

Print date: 23/04/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Monocrete Floor

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Cement based preparation for continuous coating mortars.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: Luxury Concrete, SLU

Address: C/ Lepanto n 9, 3a City: 46008, Valencia Province: Valencia

Telephone: +34 910 028 940
E-mail: info@luxuryconcrete.eu
Web: https://www.luxuryconcrete.eu/

1.4 Emergency telephone number: +34 630 352 217 (Available 24 hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Dam. 1 : Causes serious eye damage. Skin Irrit. 2 : Causes skin irritation.

Skin Sens. 1 : May cause an allergic skin reaction. STOT SE 3 : May cause respiratory irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:





Signal Word:

Danger

H statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

P statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P405 Store locked up.

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Version 1 Date of compilation: 16/11/2016

Version 4 (replaces version 3) Revision date: 31/03/2021



Page 2 of 10 Print date: 23/04/2021

P501 Dispose of contents/container to ...

Contains:

Cement, portland, chemicals

2.3 Other hazards.

The product may have the following additional risks:

Dustiness.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
CAS No: 65997-15-1 EC No: 266-043-4	[1] Cement, portland, chemicals	20 - 49.99 %	Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - STOT SE 3, H335	-
CAS No: 14808-60-7 EC No: 238-878-4	[1] crystalline silica: Quartz (SiO2) (respirable fraction)	0 - 0.99 %	-	STOT RE 2, H373: 1% < C ≤ 10% STOT RE 1, H372: C > 10%

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

^[1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Date of compilation: 16/11/2016 Version 1

Version 4 (replaces version 3) Revision date: 31/03/2021



Page 3 of 10 Print date: 23/04/2021

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Date of compilation: 16/11/2016 Version 1

Version 4 (replaces version 3)



Page 4 of 10 Revision date: 31/03/2021 Print date: 23/04/2021

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

With the exception of the indications already specified, it is not needed to carry out any special recommendation concerning the applications of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
		United Kingdom [1]	Eight hours		10 (inhalable dust) 4 (respirable dust)
			Short term		
		Éire [2]	Eight hours		1 (Respirable fraction)
			Short term		
		United States [3] (Cal/OSHA)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		
		United States [4] (NIOSH)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		
Cement, portland, chemicals	65997-15-1	United States [5] (OSHA)	Eight hours		15 (Total dust) 5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per c.c.)
	14808-60-7	Éire [2]	Short term Eight hours		0,1
crystalline silica: Quartz (SiO2)			Short term		0,1
(respirable fraction)		United States	Eight hours		0.05
, ,		[3] (Cal/OSHA)	Short term		

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Version 1 Date of compilation: 16/11/2016

Version 4 (replaces version 3) Revision date: 31/03/2021



Page 5 of 10

Print date: 23/04/2021

	T	T	
	United States [4] (NIOSH)	Eight hours	Potential occupational
			carcinogens 0.05
		Short term	0.03
		Short term	10
	United States	Eight hours	10 mg/m3/(%SiO2 +2),
			250/(%SiO2+5) (mppcf:Millions
			of particles per
			cubic foot of air, based on
			impinger
			samples counted by
	[5] (OSHA)		light-field
			techniques. Conversion
			factors - mppcf
			X 35.3 = million
			particles per cubic meter =
			particles per
			c.c.)
Ell According Limit Value (IOELV) list in 2nd Indicative O		Short term	_

- [1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.
- [2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).
- [3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
- [4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.
- [5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

_				
Concentration:	100 %			
Uses:	Cement based preparation for continuous coating mortars.			
Breathing protect	tion:			
If the recommende	ed technical measures are observed, no individual protection equipment is necessary.			
Hand protection				
PPE:	Work gloves.			
Characteristics:	«CE» marking, category I.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible.			
Maintenance:	Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or			
	adhesives.			
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.			
	Always use with clean, dry hands.			
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35			
Eye protection:				
PPE:	Protective goggles against particle impacts.			
Characteristics:	«CE» marking, category II. Eye protector against dust and smoke.			
CEN standards:	EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.			
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.			

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Date of compilation: 16/11/2016 Version 1

Version 4 (replaces version 3) **Revision date: 31/03/2021** Print date: 23/04/2021



Skin protection:

PPE: Protective clothing.

«CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics:

order not to obstruct the user's movements.

CEN standards: EN 340

In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance:

the manufacturer.

The protective clothing should offer a level of comfort in line with the level of protection provided in Observations:

terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level

of activity and the expected time of use.

PPE: Work footwear.

Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347

This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should Maintenance:

not be used by other people.

Work footwear for professional use includes protection elements aimed at protecting users against any Observations:

injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Odourless powder with characteristic colour

Colour: N.A./N.A. Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH:N.A./N.A.

Melting point: N.A./N.A. Boiling Point: N.A./N.A. Flash point: N.A./N.A. Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density: N.A./N.A. Relative density: 2,65 Solubility: N.A./N.A. Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A. Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Date of compilation: 16/11/2016 Version 1

Page 7 of 10 Print date: 23/04/2021 Version 4 (replaces version 3) Revision date: 31/03/2021



10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity:

Not conclusive data for classification.

b) skin corrosion/irritation:

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Version 1 Date of compilation: 16/11/2016

Page 8 of 10 Revision date: 31/03/2021 Version 4 (replaces version 3) Print date: 23/04/2021

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Version 1 Date of compilation: 16/11/2016

Version 4 (replaces version 3) Revision date: 31/03/2021



Page 9 of 10

Print date: 23/04/2021

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 0 % VOC content: 0 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): nwg: Not dangerous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Classification codes:

Eye Dam. 1 : Serious eye damage, Category 1 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1B : Skin sensitiser, Category 1B

STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Changes in the composition of the product (SECTION 3.2).
- Modification of exposure data (SECTION 8.1).
- Change in the hazard classification (SECTION 11.1).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

AwSV: Facility Regulations for handling substances that are hazardous for the water.

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

WGK: Water hazard classes.

(in accordance with Regulation (EU) 2015/830)

Monocrete Floor

Version 1 Date of compilation: 16/11/2016

Version 4 (replaces version 3) Revision date: 31/03/2021



Page 10 of 10 21 Print date: 23/04/2021

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/
Regulation (EU) 2015/830.
Regulation (EC) No 1907/2006.
Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.