

Concrete Finish WT Pool.

Concrete Finish WT Pool is a one-component water-based sealer for Concrete Pool that creates a protective and consolidating layer.



Technical data

Type	Water based emulsion
Appearance	Milky liquid
Solids	16,5%
PH	Between 6,5 and 7,5
Viscosity (Ford Cup 4)	10 -11 seconds
Density at 20°C	1 ± 0,01 g/mL
Application temperature	5°C to 35°C
Dry to touch	20 minutes*

(*) Depends on temperature and humidity.

Consumption

- 2 coats: 0,12 L/m².

Properties

- Improves mechanical and chemical resistance.
- Stable in humid environment.
- Resistant to microcement alkalinity.
- High adhesion.
- Easy application
- Low water absorption.
- Water-based, non-flammable.
- Permeable to water vapour.

Application

As a swimming pool sealant:

Before applying Concrete Finish WT Pool it is essential to check that the substrate is dry and free of dust. Depending on the climatic conditions and the ventilation of the working area, it is necessary to allow at least 24 hours before applying the primer to the microcement.

Apply by short pile microfibre roller in two coats, spaced 4 to 6 hours between coats.

If the sealant is applied and it rains within 7 days, this will cause staining of the sealant. It must be dried, sanded and re-varnished.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.

In case of contact with skin wash with soap and water.

Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with the legal regulations in force.

To prevent the product from drying out or thickening, close the lid after each use.

This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under current regulations, any additional labelling measures.

Keep out of reach of children.

For more information see product safety data sheet.

Packaging

It is packaged in 5 litre bottles.

Storage conditions

The product should be stored in its original closed packaging in a dry and well-ventilated place, away from away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if properly stored.

Cleaning of tools

Tools are washed with soap and water immediately after use.